

# Industrial Wet & Dry Vacuum Cleaners



**FIVE DM50 Series**

**NEW**

**FIVE DM 1/DT 1 Series**



**FIVE DM50/DM 1/DT 1 series**

- Washable panel filter with cyclone effect: it combines great filtering and high autonomy without intervention.
- Mechanical filter shaker, restores filtering action quickly without manual operations
- Filters (optional) against thin dust or HEPA • Silenced Motors • Automatic water ejection system(DM 1/DT 1) • Tough integrated accessory storage facility • Non-overturning steel structure



Technical data:	FIVE DMV50 1-22	FIVE DMX50 1-22 Inox	FIVE DMV 1-22	FIVE DMX 1-22 Inox	FIVE DTV 1-30	FIVE DTX 1-30 Inox
Code	0.045.0115	0.045.0116	0.045.0007	0.045.0008	0.045.0009	0.045.0010
Motor W	2200	2200	2200	2200	3000	3000
column depression	22,6 kPa	22,6 kPa	22,6 kPa	22,6 kPa	31,4 kPa	31,4 kPa
column depression	(2300 mm H <sub>2</sub> O)	(2300 mm H <sub>2</sub> O)	(2300 mm H <sub>2</sub> O)	(2300 mm H <sub>2</sub> O)	(3200 mm H <sub>2</sub> O)	(3200 mm H <sub>2</sub> O)
suction air	89 l/s	89 l/s	89 l/s	89 l/s	89 l/s	89 l/s
tank capacity	50 l. - 5.29 gal	50 l. - 5.29 gal	100 l. - 10.58 gal	100 l. - 10.58 gal	100 l. - 10.58 gal	100 l. - 10.58 gal
sound pressure	<74 dB(A)	<74 dB(A)	<74 dB(A)	<74 dB(A)	<74 dB(A)	<74 dB(A)
voltage	230 V~50 Hz (1Ph)	230 V~50 Hz (1Ph)	230 V~50 Hz (1Ph)	230 V~50 Hz (1Ph)	400 V~50 Hz (3Ph)	400 V~50 Hz (3Ph)
filtering surface	15000 cm <sup>2</sup>	15000 cm <sup>2</sup>	15000 cm <sup>2</sup>	15000 cm <sup>2</sup>	15000 cm <sup>2</sup>	15000 cm <sup>2</sup>