

A8



Technical data:	A8 55 T	A8 66 TA
Code	8.525.1010	8.525.1212
power supply	24V	24V
scrubbing width	550 mm	660 mm
squeegee width	800 mm	800 mm
max working capacity	2200 m ² /h	2640 m ² /h
detergent tank capacity	55 l	55 l
recovery tank capacity	55-65 l	55-65 l
traction	automatic	automatic
brush motor	600W	750W
vacuum motor	370W	350W

Standard equipment

A8 55 T



- 5.511.1113
PPL brush Ø 533 mm - 21"

A8 66 TA



- 2 x 5.511.1105
PPL brush Ø 330 mm - 13"

A8 55 T



- 4.508.X468
Front squeegee blade L.830 mm
Shore 40 Th. 2.5 mm
- 4.508.X467
Rear squeegee blade L.870 mm
Shore 40 Th. 3 mm

A8 66 TA

- 4.508.1524
Front squeegee blade L.860 mm
Shore 33 Th. 4 mm
- 4.508.1523
Rear squeegee blade L.900 mm
Shore 40 Th. 4 mm



- 0.108.0059
On-board Battery charger
CBHD1-XR 24V 12A

A8

- Designed for the maintenance and deep cleaning of large areas (up to 1.700 m²)
- Especially suitable for cleaning: car shops, sales points, gym, health care
- User friendly control panel
- Automatic brush lifting (model 66BTA only)
- Fully accessible recovery water tank with visual inspection
- Front/rear lighting system (optional)
- Automatic detergent measuring system (model 66BTA only)
- Big size traction wheels
- Handle with control lever (models 55BT/66BTA)