

Sundek5



mod. Sundek5 -55Y-75Y



Sundek5

- 4 poles electrical motor (1450 RPM) with thermal protection (Sundek5 31Y-55Y-75Y) • water cooling (mod. Sundek5 -55Y-75Y) • Three ceramic coated pistons, brass axial pump head with built-in by-pass valve. • Vertical burner with high thermal efficiency steel coil. • Suction and delivery S/S valves. • Safety valve.
- Temperature regulation gauge. • Glycerine pressure gauge.
- AUTOMATIC STOP System late shut down protection 24V.
- Header tank (Sundek5-55Y-75Y) • Swivel hose/gun fitting
- Adjustable detergent delivery with built-in tank for indirect suction.
- Auxiliary motor for burner air-cooling (Sundek5 31Y-55Y-75Y)
- Two ways fuel pum • Low fuel lamp. • Ergonomic handles and impact resistant covers. • Accessory holder. • Power cable (m 5).

Standard equipment:

- High pressure gun with quick swivel hose coupling • High pressure hose 10 mt • High pressure lance with high /low pressure regulation • Inlet brass quick fitting • High pressure nozzle • Outlet-hose quick fitting

Optional:

- Hose-reel with brake.
- Header tank with (Sundek5 31Y)
- Header tank with antiscal tank (Sundek5 31Y-55Y-75Y)
- Antiscal LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044

Technical data:	Sundek5 30	Sundek5 40	Sundek5 31Y	Sundek5 55Y	Sundek5 75Y
Code	8.620.0008	8.620.0009	8.621.0805	8.621.0824	8.621.0825
Operat. pressure bar	30 ÷ 120	30 ÷ 150	30 ÷ 110	30 ÷ 150	30 ÷ 200
Operat. pressure psi	435 ÷ 1740	435 ÷ 2175	435 ÷ 1590	435 ÷ 2175	435 ÷ 2900
l/h	330 ÷ 660	330 ÷ 660	330 ÷ 660	450 ÷ 900	450 ÷ 900
max water temperature	140°C	140°C	140°C	140°C	140°C
Abs. power kW	3,2	4	3	5,5	7,3
RPM	2800	2800	1450	1450	1450
Voltage	230 V~50 Hz	400 V~50 Hz	230 V~50 Hz	400 V~50 Hz	400 V~50 Hz